

Ref. 1PULD50

### Handling and Precision Works

### Dry Environment



### The +

**COVERPERF DURABILITY:** Washability - Performance guaranteed up to 5 cycles at 40°C  
 Touchscreen  
 Extended service life (Abrasion 4)  
 Close fitting  
 Silicone-free according to VDMA test

### PURCHASE PACKAGING

Ref.	Size	Inner	Carton
1PULD50006	6	10	100
1PULD50007	7	10	100
1PULD50008	8	10	100
1PULD50009	9	10	100
1PULD50010	10	10	100
1PULD50011	11	10	100
1PULD50012	12	10	100

### SALES PACKAGING

Hangable individual polybag

See also

### VARIANTS



1PULD40

### DESCRIPTION

EUROLITE P500 gloves, grey fine polyamide seamless support, 13 gauge, Grey polyurethane palm coating, DMF level < 30ppm; Knitted wrist, Touchscreen index;

VDMA TEST RESULTS:

- solvent-based paint the gloves are Labs-conform on all classes (A1, A2 and A3) -> VDMA24364-A1/A2/A3-L

- water-based paint the gloves are conform on all classes (A1, A2 and A3) --> VDMA24364-A1/A2/A3-W

### SECTORS

Mechanicals constructions

Light Industries

Maintenance

Services and distribution

### APPLICATIONS

Fine handling and precise assembly of parts, meticulous assembly work, sorting of small parts, small screws and bolts, assembly of electronic components.

Especially recommended for painting, automotive industries, car bodywork, epoxy, solvents...

**TECHNICAL FEATURES**



Gauge 13

Color	Grey
Color 2	Grey
Shape	Glove
Gloves environment	Dry environment
Glove type	Seamless knitting
Support material	Polyamide
Coating level	Palm
Material of coating	PU
Coating finition	Smooth
Type Of Cuff	Elastic wrist

**STANDARD(S)**

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate in progress

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 21420:2020

Protective gloves – General requirements and test methods

EN388:2016  
+ A1:2018



4.1.2.1.X.

Protection from mechanical risks

COVERPERF -  
Durability/Washable



RETAILER STAMP

MAJ 11/07/2023