

Ref. **9GAL120**

Indoor and dry environments

Low

Low shoes



### The +

Lightweight (430 g in size 42)  
Flexible and cushioning  
Breathable

#### PURCHASE PACKAGING

Ref.	Size	Carton
9GAL120036	36	6
9GAL120037	37	6
9GAL120038	38	6
9GAL120039	39	6
9GAL120040	40	6
9GAL120041	41	6
9GAL120042	42	6
9GAL120043	43	6
9GAL120044	44	6
9GAL120045	45	6
9GAL120046	46	6
9GAL120047	47	6
9GAL120048	48	6

*Some sizes may only be available in certain countries*

*See also*

#### VARIANTS



9GAL130

#### DESCRIPTION

The GALAXITE ESD HRO sneaker is very lightweight, flexible and breathable: at the forefront of comfort.

Its EVA/rubber outsole offers excellent cushioning, durability and grip.

GALAXITE is metal free. It features a composite toe-cap and an anti-penetration plate made of textile which ensure both protection and flexibility. This shoe is ideal for work environments such as logistics, construction finishing works or DIY.

#### SECTORS

Light Industries

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

**TECHNICAL FEATURES**

Color	Black	Insole	Removable, perforated EVA
Color 2	Blue	Reinforce-ment material	TPU
Weight	425 g	Reinforce-ment location	Front
Upper	Mesh	Closing	Lacing closure
Toecap	Composite	Lining	Breathable 3D mesh
Puncture resistant sole	Textile		
Midsole	EVA		
Outsole	Rubber nitrile		

**INSTRUCTION FOR USE AND STORAGE**

**Instructi-ons for use**

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

**Storage instructi-ons**

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

**Washing instructi-ons**

Regularly clean the shoes by using brushes, cleaning clothes.

**STANDARD(S)**

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/05/21/0808 EXT 01/05/21

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

**HRO**

Heat contact resistant outsole (60 seconds at 300°C)

**ESD**

Electrostatic discharge shoe (CEI EN 61340-4-3 standard)

**COVERPERF - Breathability**



Shoes tested in a certified laboratory (CTC) offering excellent breathability. Removal of perspiration above 4g/h.

**COVERPERF - Damping**



Shoes tested in a certified laboratory (CTC) offering excellent damping. Over 25% of the impact force is absorbed by the sole.

**EN ISO 20345:2022**

**S1PS**

**Safety shoes**

**S1PS** Basic requirements: a protective toe cap resistant to an impact of 200 Joule and a crushing of 15,000 Newton + closed heel area- antistatic properties- energy-absorbing capacity of the heel + Puncture resistance:- Resistance of the sole to puncture (min.1100 N and individual value ≥ 950 N) - Non-metallic insert, 3.0mm diameter puncture needle

**SR**

Resistance to slippage (ceramic floor + oil)

**FO**

Hydrocarbons resistance

MAJ 16/10/2024