

Ref. **9GAL130**

Indoor and dry environments

Low

Low shoes



The +

Lightweight (430 g in size 42)
Flexible and cushioning
Breathable

PURCHASE PACKAGING

Ref.	Size	Carton
9GAL130037	37	6
9GAL130038	38	6
9GAL130039	39	6
9GAL130040	40	6
9GAL130041	41	6
9GAL130042	42	6
9GAL130043	43	6
9GAL130044	44	6
9GAL130045	45	6
9GAL130046	46	6
9GAL130047	47	6

Some sizes may only be available in certain countries

See also

DESCRIPTION

The GALAXITE ESD HRO sneaker is very lightweight, flexible and breathable: at the forefront of comfort.

Its EVA/rubber outsole offers excellent cushioning, durability and grip.

GALAXITE is metal free. It features a composite toe-cap and an anti-penetration plate made of textile which ensure both protection and flexibility. This shoe is ideal for work environments such as logistics, construction finishing works or DIY.

SECTORS

Light Industries

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

VARIANTS



9GAL120

TECHNICAL FEATURES

Color	Black	Insole	Removable, perforated EVA
Color 2	Red	Reinforce-ment material	TPU
Weight	430 g	Reinforce-ment location	Front
Upper	Mesh	Closing	Lacing closure
Toecap	Composite	Lining	Breathable 3D mesh
Puncture resistant sole	Textile		
Midsole	EVA		
Outsole	Rubber nitrile		

INSTRUCTION FOR USE AND STORAGE

Instructi-ons for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructi-ons

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructi-ons

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/05/21/0808

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

HRO

Heat contact resistant outsole (60 seconds at 300°C)

ESD

Electrostatic discharge shoe (CEI EN 61340-4-3 standard)

COVERPERF - Damping



Shoes tested in a certified laboratory (CTC) offering excellent damping. Over 25% of the impact force is absorbed by the sole.

EN ISO 20345:2022

S1PS

Safety shoes

S1PS Basic requirements: a protective toe cap resistant to an impact of 200 Joule and a crushing of 15,000 Newton + closed heel area- antistatic properties- energy-absorbing capacity of the heel + Puncture resistance:- Resistance of the sole to puncture (min.1100 N and individual value ≥ 950 N) - Non-metallic insert, 3.0mm diameter puncture needle

SR

Resistance to slippage (ceramic floor + oil)

FO

Hydrocarbons resistance