

Ref. **9GRAH**

Outdoor

High

High shoes



S3



0%  
METAL

### The +

- \* Breathable upper and lining.
- \* Padded collar, ankles and bellows tongue for snug fit.
- \* Heel and toe scuff caps for a longer shoe's lifespan.

### PURCHASE PACKAGING

Ref.	Size	Carton
9GRAH37	37	
9GRAH38	38	10
9GRAH39	39	10
9GRAH40	40	10
9GRAH41	41	10
9GRAH42	42	10
9GRAH43	43	10
9GRAH44	44	10
9GRAH45	45	10
9GRAH46	46	10
9GRAH47	47	10
9GRAH48	48	

*Some sizes may only be available in certain countries*

### DESCRIPTION

Composite toecap  
Antipenetration textile sole  
External sole in double density PU/PU  
Breathable mesh lining  
Upper in full grain leather  
Reinforcement : front and back in TPU

### SECTORS

Mining  
Extracting Oil and Gas  
Energy (production and distribution)  
Infrastructure, building industry

### APPLICATIONS

Builder,  
Slater,  
Ramp agent,  
Luggage handler,  
Site supervisor,  
Dockers, ...

## TECHNICAL FEATURES

Color	Brown	Insole	Removable, textile and foam
Color 2	Orange	Main assembly	Injected
Weight	643 g	Reinforcement material	Anti-abrasion Stark®
Upper	Full grain leather / Polyamide mesh	Reinforcement location	Heel / Front
Toecap	Composite	Closing	Lacing closure
Puncture resistant sole	Textile	Lining	Breathable 3D mesh
Midsole	PU		
Outsole	PU		

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **LEC F100338957**

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom



EPI CAT. II

EN ISO 20345:2011

S3

SRC

Safety shoes

**S3** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol