

Ref. **9GRAP10**

Indoor and dry environments

Low

Low shoes



### The +

Comfortable  
 Technical insole: shock and moisture absorption, anti-odor  
 Reflective stripes: visibility  
 Urban style

### PURCHASE PACKAGING

Ref.	Size	Carton
9GRAP10036	36	6
9GRAP10037	37	6
9GRAP10038	38	6
9GRAP10039	39	6
9GRAP10040	40	6
9GRAP10041	41	6
9GRAP10042	42	6
9GRAP10043	43	6
9GRAP10044	44	6
9GRAP10045	45	6
9GRAP10046	46	6
9GRAP10047	47	6
9GRAP10048	48	6

*Some sizes may only be available in certain countries*

### DESCRIPTION

The ESD GRAPHITE sneaker is designed for comfort. Its insole is anti-odor, and equipped with gel inserts and EVA allowing shock absorption. Its EVA/Rubber outsole offers excellent cushioning, durability and grip. GRAPHITE features a composite toe-cap and an anti-penetration plate made of textile which ensure both protection and flexibility. GRAPHITE is a sneaker with a discreet look that can easily be combined with different types of outfits.

### SECTORS

Light Industries

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

## TECHNICAL FEATURES

Color	Black	Closing	Lacing closure
Weight	506 g	Lining	Breathable 3D mesh
Upper	Suede leather / Mesh		
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	EVA		
Outsole	Rubber nitrile		
Insole	Removable, perforated EVA		

## INSTRUCTION FOR USE AND STORAGE

## Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

## Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

## Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

## STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/05/21/0808EXT02/05/21

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S1P

Safety shoes

**S1P** Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

ESD

Electrostatic discharge shoe (CEI EN 61340-4-3 standard)

COVERPERF - Damping



Shoes tested in a certified laboratory (CTC) offering excellent damping. Over 25% of the impact force is absorbed by the sole.