

Indoor

High

High shoes



HRO



The +

- * Breathable upper and lining.
- * Padded collar and bellows tongue for snug fit.

PURCHASE PACKAGING

Référence	Taille	Carton
9HILH39	39	10
9HILH40	40	10
9HILH41	41	10
9HILH42	42	10
9HILH43	43	10
9HILH44	44	10
9HILH45	45	10
9HILH46	46	10

DESCRIPTION

Composite toecap
 Antipenetration textile Wellmax® sole
 External sole in Rubber
 Reinforcement : front in Nubuck
 Textile tightening loops, High shoes plastic hooks
 Padded collar
 Upper in Nubuck
 Breathable mesh lining
 Padded tongue

SECTORS

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

APPLICATIONS

Painter,
 Electrician,
 Storekeeper, ...

TECHNICAL FEATURES

Color	Black	Lining	Breathable 3D mesh
Color 2	Grey		
Upper	Polyamide mesh / Nubuck leather		
Toecap	Composite		
Puncture resistant sole	Textile		
Outsole	Rubber nitrile		
Insole	Removable, textile and foam		
Main assembly	Cemented		
Closing	Lacing closure		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **LEC FI00330566**

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom

**EPI CAT. II****EN ISO 20345:2011****S1P**

Safety shoes

S1P Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe $0,1M\Omega < A < 1000 M\Omega$ + Fuel and oil resistant contact outsole + Energy absorbing heel $E \geq 20$ Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure

SRA

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

HRO

Heat contact resistant outsole (60 seconds at 300°C)

RETAILER STAMP