

Ref. **9IOLH10**

Specialties

High

High shoes



S3



The +

- *PU/PU outsole: impact cushioning. Protects the back and joints.
- *Outsole with numerous notches: easy flexing and comfort when walking.
- *Grooves for liquid dispersment: reduces slipping.
- *Discreet feminine look.

PURCHASE PACKAGING

Ref.	Size	Carton
9IOLH10036	36	6
9IOLH10037	37	6
9IOLH10038	38	6
9IOLH10039	39	6
9IOLH10040	40	6
9IOLH10041	41	6

Some sizes may only be available in certain countries

DESCRIPTION

Feminine and discreet, the IOLITE shoe is a comfortable model that matches a lifestyle that is always on the move.

The burnt-effect suede leather goes perfectly with the copper color.

In order to promote flexibility and lightness, the protective toe cap and the anti-perforation sole of the shoe are made respectively of composite material and textile.

Its double density PU outsole resists to fuel and oil contact. It is slip-resistant on ceramic or steel floor and offers excellent shock absorption. IOLITE is the ideal safety shoe for the modern woman.

SECTORS

Regional/public authorities

Construction - finishing work

Transport (excluding manufacturing) and logistics

TECHNICAL FEATURES

Color	Black	Insole	HI-POLY foam
Color 2	Copper	Main assembly	Injected
Weight	502 g	Closing	Lacing closure
Upper	Suede leather	Lining	Breathable 3D mesh
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	PU		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/08/21/1366 EXT 01/08/21

Delivered by CTC (0075) 4 rue Hermann. Frenkel 69367 Lyon Cedex 07 France



EPI CAT. II

EN ISO 20345:2011

S3

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol