

Ref. **9KASL**

Specialties

Low

Low shoes



S1P



HRO



The +

- * Lightweight for use all day long.
- * Breathable upper and lining.
- * Padding for snug fit.

PURCHASE PACKAGING

Ref.	Size	Carton
9KASL35	35	10
9KASL36	36	10
9KASL37	37	10
9KASL38	38	10
9KASL39	39	10
9KASL40	40	10
9KASL41	41	10

Some sizes may only be available in certain countries

DESCRIPTION

Composite toecap
 Antipenetration textile Wellmax sole
 External sole in double density EVA/Rubber
 Upper in Suede
 Padded collar
 Non woven lining
 Padded tongue

SECTORS

Food-processing industry

Regional/public authorities

Construction - finishing work

Transport (excluding manufacturing) and logistics

TECHNICAL FEATURES

Color	Brown	Insole	Removable, textile and foam
Color 2	Orange	Main assembly	Cemented
Weight	445 g	Closing	Lacing closure
Upper	Suede leather / Polyamide mesh	Lining	Moisture wicking non-woven membrane
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	EVA		
Outsole	Rubber nitrile		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **LEC F100330999**

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom



EPI CAT. II

EN ISO 20345:2011

S1P

SRA

HRO

Safety shoes

S1P Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

Heat contact resistant outsole (60 seconds at 300°C)