

Thermal Protection

Heat Resistance



PURCHASE PACKAGING

Ref.	Size	Inner	Carton
GAN4673	10	5	

SALES PACKAGING



Individual polybag

DESCRIPTION

- * 790 g/m2 thick, highly heat- and cut-proof, looped KEVLAR thread
- * heat- and cut-proof 500 g/m2 aramid-thread inside lining
- * plus 200 g/m2 mid-lining
- * protecting for 15 sec. at 500 °C contact heat
- * GAN4673: 31 cm, five-finger design
- * size: 10
- * pac

SECTORS

- Extracting Oil and Gas
- Heavy & process industries
- Energy (production and distribution)
- Maintenance

APPLICATIONS

General and heavy handling of sharp and hot objects (aluminium/metal profiles), handling in metallurgy and steel industry.

TECHNICAL FEATURES

Color	Yellow
Shape	Glove
Gloves environment	Extreme heat
Glove type	Seamless knitting
Support material	
Material of coating	Without
Seams material	Kevlar
Lining material	
Type Of Cuff	Safety cuff
Length - mm	310

STANDARD(S)

This glove conforms to the personal protective equipment model covered by the EC type-examination certificate 22/5187/00/0161

Delivered by AITEX (0161) Plaza Emilio Sala- 1 - 03801 ALCOY (Alicante) - Espagne



EPI CAT. III

EN420:2003 + A1:2009

General requirements for protective gloves

EN388:2016



2.X.4.4.F.

Protection from mechanical risks

EN407:2004



4.4.4.4.X.X

Protection from heat and fire